

Datacard Photo Pointe™: Capture Software



USING PHOTO POINTE SOLUTIONS HELPS ENSURE CRISP, LIFE-LIKE CLARITY FOR YOUR FULL-COLOR DIGITAL IMAGES.

CHOOSE THE SOLUTION THAT MEETS YOUR NEEDS AND FITS YOUR BUDGET

- THE STANDARD PHOTO POINTE SOLUTION COMES WITH PHOTO POINTE SOFTWARE, AN 8 MEGAPIXEL DIGITAL CAMERA AND IMAGE CAPTURE ACCESSORIES.
- THE PHOTO POINTE PRO SOLUTION INCLUDES PHOTO POINTE SOFTWARE, AN 12.1 MEGAPIXEL CAMERA, IMAGE CAPTURE ACCESSORIES AND AN OPTIONAL HIGH-POWERED EXTERNAL FLASH.

The Datacard® Photo Pointe™ Capture Software offers fast and easy image capture.

Add speed and productivity to any photo ID process with Datacard® Photo Pointe™ solutions. Photo Pointe software — part of the Datacard® Capture Pointe™ Series software family — makes image capture easy. One click allows you to capture, crop and produce a high-quality digital image in less than three seconds. No panning, tilting, zooming or other camera adjustments are required. Fully compatible with products from our software and hardware families, Photo Pointe™ solutions make a powerful addition to any integrated photo ID system from Datacard Group.

As the largest integrator in the southwest, RockWest Technology Group offers complete identification, access control and accountability solutions engineered to meet your needs. Our local sales, service, and support are available to assist with all of your identification needs.



Sales, Service, & Supplies



888.383.6083 tel 888.916.0164 fax



www.RockWestTech.com

Datacard Photo Pointe™: Capture Software



Using your pre-sets for capturing and cropping, Photo Pointe software can produce a high-quality digital image in less than seven seconds.

End-user definable software settings

- Auto capture
- Manual capture of live video
- Auto crop image at a pre-defined ratio
- Manual crop
- White balance environment
- Red-eye reduction

Photo Pointe solution components

- Photo Pointe software with USB security key
- 4.0 megapixel digital camera
- Standard 4-ft. USB cable and 10-ft. USB extension cable
- AC power adapter
- Country-specific power cord
- Tripod, backdrop, stand and frame
- Installation instructions

Photo Pointe solution specifications

- Camera dimensions: W 3.57 in. x H 2.52 in. x D 1.51 in. (90.7 mm x 64.0 mm x 38.4 mm), excluding protrusion
- Weights 6.35 oz./180g (camera body only)
- Operates in temperatures from 32° to 104° F (0° to 40° C) with humidity levels of 10% to 90%
- 4x optical zoom
- Flash range of 2 to 6 feet (0.6 to 1.8 meters) from camera
- Multimedia Card (MMC-16M)
- CE Mark certified, FCC Class B, UL

Photo Pointe Pro solution components

- Photo Pointe software with USB security key
- 7.1 megapixel digital camera
- Standard 4-ft. USB cable and 10-ft. USB extension cable
- AC power adapter
- Country-specific power cord
- Tripod, backdrop, stand and frame
- Installation instructions
- Optional external flash (120V/240V) components include flash, bracket, synchro cord, hot shoe adapter and country-specific power cord

Photo Pointe Pro solution specifications

- Camera dimensions: W 4.1 in. x H 2.9 in. x D 2.9 in. (104.9 mm x 72.8 mm x 73.1 mm)
- Weights 13.4 oz./380g (camera body only)
- Operates in temperatures from 32° to 104° F (0° to 40° C) with humidity levels of 10% to 90%
- 4x optical zoom
- Flash range of 2 to 6 feet (0.6 to 1.8 meters) from camera
- SanDisk® CompactFlash® Card (FC-32M)
- CE Mark certified, FCC Class B, UL

Optional external flash specifications

- Adjustable for full, half and quarter power
- Three-second recycle time
- 50,000 flash lifespan (at full power)
- Recommended distance of 6 to 15 feet (1.8 to 4.5 meters)



RockWest Technology Group



888.383.6083 tel 888.916.0164 fax



www.RockWestTech.com